

Ku-band block upconverters in 1U 19" chassis with independent PSU and 10MHz reference

INPUT SPECIFICATION

1. Frequency range:	950MHz to 1,700MHz (check model table)
2. Connector:	SMA
3. Impedance:	50Ω
4. Return loss:	≥15dB typical

OUTPUT SPECIFICATION

5. Frequency range:	12.75GHz to 14.5GHz (check model table)
6. Connector:	SMA
7. Impedance:	50Ω
8. Return loss:	≥18dB
9. 1dB compression point:	+10dBm

TRANSFER CHARACTERISTICS

10. Gain:	15dB (±1dB), fixed	25dB (±1dB), fixed
11. Gain stability: from 0°C to +50°C: over 24 hours, constant temp.	≤ 2dB ≤ 0.4dB	
12. Gain ripple: over any 40MHz transponder: over 500/750MHz output band:	≤0.5dB p.t.p. ≤1.5dB p.t.p	
13. External reference:	10MHz, 0dBm nominal	
14. Local Oscillator:	11.8GHz, 12.8GHz, 13.05GHz (check model table)	
15. Noise figure:	<20dB	

Spurii

16. From 0 to 15GHz (at 0dBm output):	≤-60dBm
---------------------------------------	---------

PHASE NOISE

17. 10Hz:	<-40dBc/Hz
18. 100Hz:	<-65dBc/Hz
19. 1kHz:	<-75dBc/Hz
20. 10kHz:	<-85dBc/Hz
21. 100kHz:	<-95dBc/Hz
22. 1MHz:	<-100dBc/Hz
23. Mains related:	<-50dBc/Hz

MISCELLANEOUS

24. Power supply:	115V/230V ±10%, 50/60Hz ±10%, 30VA.
25. Mechanical:	1U 19" frame, 400mm deep
26. Temperature:	Operating: 0° to +50°C Storage: -50° to +70°C
27. Summary alarm:	NO and NC dry relay contacts via rear mounted connector
28. Summary alarm indication:	Through front panel LED
29. Remote interface:	Serial RS232/RS485 plus SNMP and web browser

MODEL TABLE

Model	Input band, MHz	Output band, GHz	LO, GHz
BU701	950 to 1,450	14.00 to 14.50	13.05
BU711	950 to 1,450	12.75 to 13.25	11.80
BU731	950 to 1,700	13.75 to 14.50	12.80
BU751 ⁽¹⁾	950 to 1,450 plus 950 to 1,750	12.75 to 13.25 plus 13.75 to 14.50	11.80 plus 12.80

⁽¹⁾ Dual band, single input, single output, active band selectable via front panel.

Note: Specification subject to change at any time without prior notice.