

MDT661 ANDROID MOBILE PHONE



Android Rugged Mobile Phone

# MDT661

The Best Rugged Smart Phone for Tough Field Work



#### OS

Android 9.0



#### Performance

Octa-Core Processor



#### Wireless

Wifi, Bluetooth



#### Battery

Long-lasting 4000mAh



#### Operating Temp.

-10°C to 60°C



#### Camera

16MP Autofocus with flash



#### Display

6" (1440 x 720)



#### Drop Resistance

Multiple 1.2 m (4 ft) drops per MIL STD 810G

#### Cradle Design

RS232 interface

#### Network

2G / 3G / 4G with voice; Proved reliability network connection

#### Extended Features

Barcode reader

#### RFID

Back access, easy for login

#### MDM Remote Control Server

Topicon's device management server is developed to allow customer to update different firmware and make kiosk mode

#### MDM server function:

- BOOT ANIMATION
- INSTALL APK
- ADD APN
- DEFAULT SETTING
- CUSTOMIZED BUTTON



## Specification

### PERFORMANCE CHARACTERISTICS

CPU	2.0GHz Octa Core Processor
OS	Android 9.0 with GMS or without GMS (Optional)
Memory	4GB LPDDR4X 32GB eMMC

### PHYSICAL CHARACTERISTICS

Dimensions	161.5mm L x 77.5mm W x 14.5mm D
Weight	280g
Display	5.7inch, IPS panel (1440 x 720 pixel)
Touch Panel	Capacitive multi-touch / Glove, Wet, Stylus
Backlight	LED Backlight
Power	Battery 3.7V 4000mAh
Expansion Slot	User accessible micro SDXC card slot (standard supports up to 2TB)
SIM	Dual-SIM card slot
Interface	Docking Connector (8pin) USB Type C (2.0) (OTG)
Notification	Audible tone
Voice / Audio	Speaker, Microphone, headphone
Keypad	On-screen keypad

### WIRELESS WAN DATA AND VOICE COMMUNICATION

Radio Frequency	EUR - (Europe market) GSM: 900/1800MHz WCDMA: 850/900/2100MHz FDD (4G): B1/B3/B5/B7/B8/B20 TDD (4G): B38/B40/B41 NAR - (North America market) GSM: 850/1900MHz WCDMA: 850/1700/1900MHz FDD (4G): B2/B4/B5/B12/B17 TDD (4G): B38/B40/B41
GPS	GNASS, GLONASS, GALILEO, A GPS,

### WIRELESS LAN

Radio	802.11 b/g/n/ac 802.11 d/e/h/i/j/k/r/v/w IPv4, IPv6
Data Rate	5GHz: 802.11a/n/ac — up to 500 Mbps; 2.4GHz: 802.11b/g/n — up to 144Mbps
Security and Encryption	WFA WPA/WPA2 Personal, AES-CCMP, WPI-SMS4, GCMP, WPS2.0, WAPI (hardware)

### WIRELESS PAN

Bluetooth	v2.1+EDR, 3.0+HS, v4.1+HS
-----------	---------------------------

### DATA CAPTURE

Scanning (Optional)	1D&2D Imager (w/Smart Plug)
Camera	Rear: 16MP Autofocus Front: 8MP Fixed Focus
NFC	ISO 15693, MiFare, DesFile
Serial Communication	USB or RS232 (default with docking station)

### SENSOR

Ambient Sensor	Light sensor, Proximity sensor
Motion Sensor	Accelerometer, E-Compass, Gyroscope

### USER ENVIRONMENT

Operating Temp.	-10°C to 60°C / -14° F to 140° F
Storage Temp.	-20°C to 70°C / -4°F to 158°F
Humidity	90% non-condensing
Drop Spec.	1.2m / 4 ft. to drop per MIL STD 810G
Sealing	IP67
Electrostatic Discharge (ESD)	+/-8kVdc air discharge +/-4kVdc direct discharge

### OPTIONAL ACCESSORIES

Vehicle docking station Motorcycle docking station
---

### OPTIONAL FEATURES

FM broadcasting Fingerprint
--------------------------------

\* Specification is subject to change.