



STANDARD
MIL-STD
461F

STANDARD
MIL-STD
188-164A

STANDARD
MIL-STD
810G

PFA-240-MIL

Whether you operate in Ku, Ka, X, C and DBS Band, the PFA-240-SPL could be easily configured with and interchangeable feed to provide instant satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. It ensures reliable transmission for any applications such as broadcast, corporate networks, military and emergency communications, etc...

It can be easily transported with IATA weight-compliant flight cases so it can be transported by a commercial airline to wherever you need it.

The PFA-240-SPL with its lightweight but robust segmented Carbon-Fiber main reflector facilitates easy and fast deployment. Two operators can achieve the installation within 12 minutes without any training and tools required.

COMPATIBILITY

- MIL-STD-810G Compliant
- MIL-STD-461F Compliant
- MIL-STD-1472 Compliant
- MIL-STD-188-164A Compliant
- ITU-RS-580 Compliant
- ITU-RS-465-6 Compliant
- EUTELSAT Compliant

Key Features

- C, X, Ku, Ka Band options are available
- Multi-Band feeds switch in minutes
- Multiple mount options (mobile, pedestal, tactical, tripod, trailer mounts)
- 10 reflector panels (carbon-fiber)
- Motorized or manual versions
- 2 transport cases (standard)
- Installation within 15 minutes
- Designed to comply with Mil-Spec standards
- Integrated DVB-S/S2 & Beacon Receiver
- Optional De-Ice
- Manual drive tool kit for emergency situations
- High gain, low side-lobe, high accuracy and very good cross polar rejection (> 35 dB)
- Supports OpenAmp



GENERAL SPECIFICATIONS	
Reflector Diameter	2.4m
Reflector Type	Circular, axially symmetric with 10 carbon-fiber panels, prime focus feed
Operation On-Air Time	~ 3 Minutes after Set-Up
Antenna Concept	Portable design with pedestal, trailer, tactical, tripod, mobile mounts.

RF CHARACTERISTIC		
Frequency (GHz)	Tx 13.75 - 14.50 GHz	Rx 10.70 - 12.75 GHz
Antenna Gain (± 0.2 dBi)	Tx 49.2 dBi @ Midband	Rx 47.4 dBi @Midband
Polarization	Linear	
Feed Insertion Loss	Tx 0.8 dB	Rx 0.3 dB
Waveguide Interface	WR - 75	
VSWR	1.3:1	
Cross-Polar Isolation	35 dB	
G / T	28.5 dB/K	

OTHER FEED OPTIONS				
		C-Band	X-Band	Ka-Band
Frequency	Tx	5.850-6.65 GHz	7.90-8.40 GHz	27.50-31.00 GHz
	Rx	3.625-4.200 GHz	7.25-7.75 GHz	17.70-21.20 GHz
Gain	Tx	42 @ 6.00GHz	44.4 @8.15GHz	55.2 @30.00GHz
	Rx	37.6 @4.00GHz	43.5 @7.50GHz	52.3 @20.00GHz

MECHANICAL SPECIFICATIONS				
		Azimuth	Elevation	Polarization
Drive Rates		0.3° /s	0.5° /s	0.5° /s
Antenna Travels		$\pm 180^\circ$ *	0° to 90°	$\pm 90^\circ$
*: Antenna azimuth travel range is +/-180° when elevation is greater than 36°, Antenna azimuth travel range is +/-60° from local 150° when elevation is less than 36°				
Manual Override Mechanism		Manual override for elevation and azimuth drive system		
Mount Type		Elevation over Azimuth		
Operational Limits		Hardware and software settable		

ENVIRONMENTAL SPECIFICATIONS		
Temperature	Operational	-30°C to +60°C
	Survival	-40°C to +70°C
Wind Speed	Operational	60 km/h (optional 72 km/h with pedestal mount)
	Survival	120 km/h (optional 150 km/h with pedestal mount)
Humidity (Relative)	0-100%	
Altitude	4000 m	

PACKAGING	
Carbon-Fiber Cases	Box1: 100cmx100cmx65cm Box2: 100cmx100cmx60cm

TURKEY

P : +90 216 540 72 57
M : sales@pals.com.tr
W : www.pals.com.tr

NETHERLANDS

P : +31 6 85 52 63 16
M : sales@pals-comsat.com
W : www.pals-comsat.com

